



1213

No027-DoP-2022-02-14

Standard	Title: Geotextiles and geotextile-related products	Intended Use
EN 13249:2016	Characteristics required for use in the construction of roads and other trafficked areas	F, F + S
EN 13250:2016	Characteristics required for use in the construction of railways	F, F + S
EN 13251:2016	Characteristics required for use in earthworks, foundations and retaining structures	F, F + S
EN 13252:2016	Characteristics required for use in drainage systems	F, F + S
EN 13253:2016	Characteristics required for use in erosion control works	F, F + S
EN 13254:2016	Characteristics required for use in construction of reservoirs and dams	F, F + S
EN 13255:2016	Characteristics required for use in the construction of canals	F, F + S
EN 13257:2016	Characteristics required for use in solid waste disposal	F, F + S
EN 13265:2016	Characteristics required for use in liquid waste containment projects	F

Essential Characteristics	Test Standard	Units	Performance	Confidence Limit
Tensile strength	BS EN ISO 10319	kN/m	MD 22 / CMD 22	-2.2
Elongation at maximum load	BS EN ISO 10319	%	MD 80 / CMD 80	±30
Dynamic perforation resistance	BS EN ISO 13433	mm	13	+3
Resistance to static puncture	BS EN ISO 12236	kN	3.3	-0.3
Characteristic opening size	BS EN ISO 12956	µm	60	±30
Water permeability normal to the plane	BS EN ISO 11058	l/(m ² ·s)	50	-20
Dangerous substances	National Regulations in force in EU Member States	-	Less than required by national regulations in EU Member States	-

Durability

To be covered within 1 month after installation (EN 12224).

Predicted to be durable for service lives up to 100 years in natural soils with $4 \leq \text{pH} \leq 9$ and soil temperatures $\leq 25^\circ \text{C}$ on the basis of the results of the test method EN ISO 13438 procedure A and test duration of 112 days.

System 2+: Notified factory production control certification body No. 1213 SKZ-Testing GmbH performed the initial inspection of the manufacturing plant and of factory production control (FPC) and the continuous surveillance, assessment and evaluation of FPC and issued the certificate of conformity of the FPC.

The performance of the product RK1 is in conformity with the declared performance in the table above. This declaration of performance is issued under the sole responsibility of the manufacturer Geofabrics Limited.

Signed for and on behalf of Geofabrics Limited by:

Alessandro Sartori - Technical Manager

Place and date of issue:

Leeds, West Yorkshire 14/02/2022



No027-UKDoP-2022-02-14

Standard	Title: Geotextiles and geotextile-related products	Intended Use
EN 13249:2016	Characteristics required for use in the construction of roads and other trafficked areas	F, F + S
EN 13250:2016	Characteristics required for use in the construction of railways	F, F + S
EN 13251:2016	Characteristics required for use in earthworks, foundations and retaining structures	F, F + S
EN 13252:2016	Characteristics required for use in drainage systems	F, F + S
EN 13253:2016	Characteristics required for use in erosion control works	F, F + S
EN 13254:2016	Characteristics required for use in construction of reservoirs and dams	F, F + S
EN 13255:2016	Characteristics required for use in the construction of canals	F, F + S
EN 13257:2016	Characteristics required for use in solid waste disposal	F, F + S
EN 13265:2016	Characteristics required for use in liquid waste containment projects	F

Essential Characteristics	Test Standard	Units	Performance	Confidence Limit
Tensile strength	BS EN ISO 10319	kN/m	MD 22 / CMD 22	-2.2
Elongation at maximum load	BS EN ISO 10319	%	MD 80 / CMD 80	±30
Dynamic perforation resistance	BS EN ISO 13433	mm	13	+3
Resistance to static puncture	BS EN ISO 12236	kN	3.3	-0.3
Characteristic opening size	BS EN ISO 12956	µm	60	±30
Water permeability normal to the plane	BS EN ISO 11058	l/(m ² ·s)	50	-20
Dangerous substances	National Regulations in force in the United Kingdom	-	Less than required by national regulations in the United Kingdom	-

Durability

To be covered within 1 month after installation (EN 12224).

Predicted to be durable for service lives up to 100 years in natural soils with $4 \leq \text{pH} \leq 9$ and soil temperatures $\leq 25^\circ \text{C}$ on the basis of the results of the test method EN ISO 13438 procedure A and test duration of 112 days.

System 2+: Notified factory production control certification body No. 0120 SGS United Kingdom performed the initial inspection of the manufacturing plant and of factory production control (FPC) and the continuous surveillance, assessment and evaluation of FPC and issued the certificate of conformity of the FPC.

The performance of the product RK1 is in conformity with the declared performance in the table above. This declaration of performance is issued under the sole responsibility of the manufacturer Geofabrics Limited.

Signed for and on behalf of Geofabrics Limited by:

Alessandro Sartori - Technical Manager

Place and date of issue:

Leeds, West Yorkshire 14/02/2022